§421.277

(b) Dryer vent caustic wet air pollution control.

PSNS FOR THE PRIMARY RARE EARTH METALS SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of mischmetal produced from wet rare earth chlorides	
Hexachlorobenzene	0.007 0.272 0.206 0.404	0.007 0.110 0.095 0.272

(c) Electrolytic cell water quench and scrubber.

PSNS FOR THE PRIMARY RARE EARTH METALS SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million of total produced
Hexachlorobenzene	0.094 3.474 2.629 5.165	0.094 1.409 1.221 3.474

(d) Electrolytic cell caustic wet air pollution control.

PSNS FOR THE PRIMARY RARE EARTH METALS SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of total mischmetal produced	
Hexachlorobenzene	0.000 0.000 0.000 0.000	0.000 0.000 0.000 0.000

(e) Sodium hypochlorite filter backwash.

PSNS FOR THE PRIMARY RARE EARTH METALS SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pound pounds) mischmetal	ds per million of total produced
Hexachlorobenzene	0.004	0.004

PSNS FOR THE PRIMARY RARE EARTH METALS SUBCATEGORY—Continued

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
Chromium (total)	0.134	0.054
Lead	0.101	0.047
Nickel	0.199	0.134

§421.277 [Reserved]

Subpart Z—Secondary Tantalum Subcategory

SOURCE: 50 FR 38374, Sept. 20, 1985, unless otherwise noted.

§ 421,280 Applicability: Description of the secondary tantalum subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of tantalum at secondary tantalum facilities.

§ 421.281 Specialized definitions.

For the purpose of this subpart the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

§ 421.282 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable technology currently available:

(a) Tantalum alloy leach and rinse.

BPT LIMITATIONS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pound pounds) of der produced	tantalum pow-
Copper	438.100 96.850 442.800 336.700 103.800	230.600 46.120 292.900 140.700